ARTICLE CODE	DESCRIPTION
FPI-8320	Clamp meter compact

BRAND

Fieldpiece Instruments

PRODUCT DESCRIPTION

Display: 4000 count
Backlight: 5 minute duration with auto-off. Blue color. SC260 only
Overrange: (OL) or (-OL) is displayed
Measurement rate: 3 times per second, nominal
Zero: Automatic
Operating environment: 32°F to 122°F (0°C to 50°C) at <70% relative humidity
Storage temperature: -4°F to 140°F (-20°C to 60°C), 0 to 80% RH (with battery removed)
Accuracy: Stated accuracy @ 73°F±9°F (23°C±5°C), <75%RH
Temperature coefficient: 0.1 x (specified accuracy) per °C [0°C to 19°C (32°F to 66°F), 28°C to 50° C(82°F to 122°F)]
APO (Auto Power Off): Approx. 30 minutes
Power: 9V, NEDA 1604A, IEC 6LR61 9V alkaline battery
Battery life: 200 hours typical alkaline (SC220/SC240); 150 hours typical alkaline (SC260)
Low battery indication: Battery icon blinks and “LO.bt” is displayed when the battery voltage drops below the operating level
Dimensions: 205.5mm(H) x 67.4mm(W) x 45.1mm(D)
Weight: Approx. 265g including battery
Altitude: Up to 6562 ft (2000m)
Overload protection: 600 VDC or 600VAC rms unless otherwise stated
Test leads: Use UL listed test leads that comply to UL61010-031 rated CATIII 600V or above
Included test leads are gold- plated and have removeable safety caps



SPECIFICATIONS

Net weight (kg)	1
Color	Undefined

TECHNICAL DETAILS

ETIM	EC000601
MOQ sales (Pc.)	1

RELATED PRODUCTS

FPI-9802 FPI-9803 FPI-9804 FPI-9800 FPI-9801