| ARTICLE CODE | DESCRIPTION |
| --- | --- |
| ASP-1300 | Supermarket pump Compact 4L ERRP with side inlet - 530x240x75mm |

## BRAND

Aspen Pumps - Xtra



## PRODUCT DESCRIPTION

Lightweight & slim
Low voltage at point of use
Two-stage filter to prevent growth and spread of biofilm
Plug & Play
Suitable for: refrigeration units; cold store cabinets
Perfect for: Single & multiple refrigeration units
Max. flow: 190 L/h @ 0 head
Max. rec. head: 35m
Tank capacity: 4.2L
Sound level @ 1m: 60 dB(A)
Power supply input: 100~240V AC 50/60Hz
Rated: Non continuous
Class: II appliance
Max. ambient temp.: 40°C
Inlet/Outlet: 40mm in, 10mm out
IP Protection: IPX4
Safety Switch: 3A NC/NO
Thermal protection: yes
Flammable refrigerant: designed to minimise
Equipment communication: Modbus RTU
In the box: Low Profile ERRP pump + 2m Plug & Play power cable + 11/2" BSP connector (for 40mm ID waste pipe) + Install manual

## SPECIFICATIONS

| | |
| --- | --- |
| Net weight (kg) | 0.1 |
| Color | Undefined |

## TECHNICAL DETAILS

| | |
| --- | --- |
| ETIM | EC011712 |
| Warranty period (M) | 12 |
| MOQ sales (Pc.) | 1 |