| ARTICLE CODE | DESCRIPTION |
| --- | --- |
| ELK-9016 | Cable ties 4.6x200mm - Hellerman - 100pce/pck |

## BRAND

Hellerman

## PRODUCT DESCRIPTION

Halogen-free
Operating temperature: -40°C - 85°C



## SPECIFICATIONS

| | |
| --- | --- |
| Net weight (kg) | 0.01 |
| Color | Black |

## TECHNICAL DETAILS

| | |
| --- | --- |
| ETIM | EC000046 |
| MOQ sales (Pack) | 1 |

## ATTRIBUTES

| | |
|---|---|
| Surface Protection | Untreated |
| Material Quality | Polyamide (PA) |
| Fluorescent | false |
| Halogen free | true |
| Inflammability class of insulation material according to with UL94 | V2 |
| Max bundle diameter (mm) | 49.5 |
| MIL approval | false |
| Min bundle diameter (mm) | 3.5 |
| Min tensile strength (N) | 230 |
| Solvable fastener | false |
| Text strip | None |
| Tie thickness (mm) | 1.2 |
| Type of fastening | None |
| UV-stable according to ASTM D6779 | false |
| Band width (mm) | 4.6 |
| Length belt/tape/tie (mm) | 200 |
| Operating temperature (°C) | -40 ... 85 °C |
| Mounting temperature (°C) | -20 ... 85 °C |
| VG approval | false |
| UL approval | true |
| Band closure | Plastic lip/-cam |