ARTICLE CODE	DESCRIPTION
FPI-8300	Manometer - dual port

BRAND

Fieldpiece Instruments

PRODUCT DESCRIPTION

Accuracy: Stated accuracy at 0 to 50°C (32 to 122°F): ± 1.5% FS
Battery: Single standard 9-volt battery, NEDA 1604, JIS 006P, IEC 6F22
Battery Life: 200 hours with low battery indicator on display
Operating environment: 32°F (0°C) to 12°F (50°C)
Compatible Media: Dry, non-corrosive gases
Overrange: "OL" or "-OL" is displayed
Auto-Off power: 15 minutes
Low Battery: symbol is displayed
Dimensions: 180mm (~7 1/16”)(H) x 60mm(~2 3/8”)(W) x 30mm(~1 3/16")(D)
Weight: approxiamately 195g including battery
Pressure Ports: tube connectors for 5mm (~3/16 inch) I.D. flexible tubing
Units of Measure: inWC, mmWC, mbar, PSI
Resolution: 0.01 inch WC
Accurancy/Ranges:
inWC: ±0.02 on 0.00 to ±2.00
±1.5% FS on 2.00 to ±60.0
mmWC: ±0.5 on 0.00 to ±51.0
±1.5% FS on 51.0 to ±1500
mbar: ±0.05 on 0.00 to ±5.00
±1.5% FS on 5.00 to ±150.0
psi: ±0.001 on 0.000 to ±0.07
±1.5% FS on 0.07 to ±2.000



SPECIFICATIONS

Net weight (kg)	0.6
Color	Undefined

TECHNICAL DETAILS

ETIM	EC011166
MOQ sales (Pc.)	1