ARTICLE CODE	DESCRIPTION
FPI-8321	Job link power clamp meter

BRAND

Fieldpiece Instruments

PRODUCT DESCRIPTION

Display: 10000 count dual display
Backlight: 5 minute duration with auto-off, blue color
Overrange: “OL” or “-OL” is displayed
Measurement rate: 3.3 times per second, nominal
Zero: Automatic
Operating environment: 32°F to 122°F (0°C to 50°C) at <70%RH
Storage temperature: -4°F to 140°F (-20°C to 60°C), 0 to 80%RH (with battery removed)
Accuracy: Stated accuracy @ 73°F±9°F (23°C±5°C), <75%RH
Temperature coefficient: 0.1 x (specified accuracy) per °C [0°C to 19°C (32°F to 66°F), 28°C to 50° C (82°F to 122°F)]
APO (Auto Power Off): Approx. 30 minutes
Power: Single standard 9-volt battery, NEDA 1604, JIS 006P, IEC 6F22
Battery life: 100 hours typical alkaline (No wireless, no backlight)
Low battery indication: Battery icon blinks and “batt” is displayed when the battery voltage drops below the operating level
Dimensions: 247mm(H) x 79mm(W) x 48mm(D)
Weight: Approx. 345g including battery
Altitude: Up to 6562 ft (2000m)
Overload protection: 1000VDC or 750VAC rms unless otherwise stated
Test leads: Use UL listed test leads that comply to UL61010-031 rated CATIV 600V, CATIII 1000V or above
Included test leads are gold-plated and have removable safety caps



SPECIFICATIONS

Net weight (kg)	0.6
Color	Undefined

TECHNICAL DETAILS

ETIM	EC000601
MOQ sales (Pc.)	1

RELATED PRODUCTS

FPI-9802 FPI-9800 FPI-9801 FPI-9804 FPI-9803